

Tutorial - Wrapped Leather Ends©

By Cheryl Cocco



Leather Cord
20 gauge wire
Round Nose Pliers
Chain Nose Pliers
Flush Wire Cutters
Pen or Narrow Paint Brush Handle



Form a small loop with your round nose pliers at one end of wire about 1 1/2" from one end.



Wrap your wire around the narrow jaw as shown.



Place your leather cord on top of wire as shown.
Hold wire and cord with chain nose pliers securely.



Wrap the longer piece of wire around both the cord and the short wire formed from the other end.
Keep your wraps neat and close together.



After wrapping one time keep the wire and the cord aligned.
(Leather cord is always on top of wire)



Wrap three times and then cut off remaining wire **under the cord**.



Now with wire cut you will wrap the remaining wire around the cord going over the slight hump left by the cut wire portion.
Keep wraps neat and tidy.



This shows the cut wire and the hump before wrapping.



This photo shows the cutting off of the wire under the cord.



Once you have wrapped all your wire on top of the cord...maybe 6 total wraps you are almost done.



You now need to cut off the excess CORD at the start of the wrap.



This photo shows both the cord cut off and the wrappings completed.



Now align loop so that it is centered on cord.

Now wrap the other side and don't forget to attach your clasp before you start wrapping.

